PO Box 518 620 Applegate St. Philomath, OR 97370



(541) 929-5650 Fax (541) 929-5277 www.seabird.com

# **FLNTU Characterization Sheet**

Date: June 27, 2018

S/N: FLNTURTD-5108

## **Chlorophyll Scale Factor**

Chlorophyll concentration expressed in µg/l can be derived using the equation:

CHL (µg/I) = Scale Factor x (Output - Dark Counts)

Dark Counts	Analog		Digital	
	0.070	V	43	counts
Scale Factor (SF)	6	µg/l/V	0.0072	μg/l/count
Maximum Output	4.98	V	4130	counts
Resolution	0.7	mV	1.0	counts
Ambient temperature during calibration	21.0	°C		

### Nephelometric Turbidity Unit (NTU) Scale Factor

Turbidity units expressed in NTU can be derived using the equation:

#### NTU = Scale Factor x (Output - Dark Counts)

	Analog		*	Digital	
Dark Counts	0.060	V	49	counts	
NTU Solution Value	1.76	V	1445	counts	
Scale Factor (SF)	2	NTU/V	0.0024	NTU/count	
Maximum Output	4.98	V	4130	counts	
Resolution	0.7	mV	1.0	counts	
Ambient temperature during calibration	21.0	°C			

#### Definition of terms:

Dark Counts: Signal output of the meter in clean water with black tape over detector.

NTU Solution Value: Signal output of the turbidity sensor when measuring a sample of interest.

**SF (CHL)**: Determined using the following equation:  $SF = x \div$  (output - dark counts), where x is the concentration of the solution used during instrument characterization. SF is used to derive instrument output concentration from the raw signal output of the fluorometer.

**SF (NTU)**: Scale factor is determined using the following equation:  $SF = xx \div (Output - Dark counts)$ , where xx is the value of a Formazin concentration. For example:  $12.2 \div (2011 - 50) = 0.0062$ .

Maximum Output: Maximum signal output the fluorometer is capable of.

Resolution: standard deviation of 1 minute of collected data.